DATE: **1996.07.12** Supersedes: **IRG N362**

ISO/IEC JTC 1/SC2/WG2/IRG Ideographic Rapporteur Group Secretariat: China

Source / Contribution Identifier :	tk9624r
Meeting:	@ / for SC2/WG2 #31
Issue Number:	Project Number:
Title: Draft text of clause 26 for IS/HS revision	
Keywords:	
Status :ISO/IEC JTC1/SC2/WG2/I	RG contribution
Short Description: This draft text is revised the clause 26 in the 10646-1:1993(E) for IS/HS revision.	
Proposed Conclusion / Requested Ac To be submitted at SC2/WG2 #31	ction:

Contact:

See attachment


Arguments / Text of Contribution:

Mr. Zhang Zhoucai, Rapporteur of ISO/IEC JTC 1/SC2/WG2/IRG Center of Computer & Microelectronics Industry Development Research Apartment 620-621, DaTun Road, ChaoYang District, Beijing, 100101, China Tel: +8610 6201 1118-300 Fax: +8610 6496 0428 E-mail: joezhg@public.bta.net.cn

Draft text of clause 26 for IS/HS revision

26 CJK Unified ideographs

Entries in the code tables for CJK (Chinese/Japanese/Korean) unified ideographs are arranged as follows.



The leftmost column shows the code position in ISO/IEC 10646, giving the code representation both in decimal and in hexadecimal notation.

Each of the other columns shows the graphic symbol for the character, and its coded representation, as specified in a source standard for character sets that is also identified in the table entry. Each of these source standards is assigned to one of five groups indicated by G, T, J, K, or V as shown in the lists below. In each table entry, a separate column is assigned for corresponding character (if any) from each of those groups of source standards.

An entry in any of the G, T, J, K, or V columns includes a sample graphic symbol from the source character set standard, together with its coded representation in that standard. The first line below the graphic symbol shows the coded representation in hexadecimal notation. The second line shows the coded representation in decimal notation which comprises two digits for section number followed by two digit for position number. Each of the coded representations is prefixed by a one-character source code

identification followed by a hyphen. This source code character identifies the coded character set standard from which the character is taken as shown in the lists below.

Hanzi G	S sources are
G0	GB2312-80
G1	GB12345-90 with 58 Hong Kong and 92
	Korean "Idu" characters
G3	GB7589-87 unsimplified forms
G5	GB7590-87 unsimplified forms
G7	General purpose Hanzi list for modern
	Chinese Language
G8	GB8565-88
GE	GB16500-95
Hanzi T sources are	
T1	TCA-CNS 11643-1992 1st plane
T2	TCA-CNS 11643-1992 2nd plane
T3	TCA-CNS 11643-1992 3rd plane
	with some additional characters
T4	TCA-CNS 11643-1992 4th plane

TCA-CNS 11643-1992 5th plane

TCA-CNS 11643-1992 6th plane

TCA-CNS 11643-1992 7th plane

TCA-CNS 11643-1992 15th plane

Kanji J sources are J0 JIS X 0208-1990 J1 JIS X 0212-1990

T5

T6

T7

TF

Hanja K sources are K0 KS C 5601-1987 K1 KS C 5657-1991 K2 PKS C 5700-1 1994

ChuNom V sources are V0 TCVN 5773:1993 V1 TCVN 6056:1995

For CJK (Chinese/Japanese/Korean) ideographs in the BMP, the names shall be algorithmically constructed by appending their two-octet coded representation in hexadecimal notation to "CJK UNIFIED IDEOGRAPH-". For example, the first CJK ideograph character in the BMP has the name "CJK UNIFIED IDEOGRAPH-4E00".

Attachment:

Differences between clause 26 of ISO/IEC 10646-1:1993(E) and this revision

Left col. Figure

- Add V column

Left col. 3rd paragraph

- Source groups (4 groups -> 5 groups, G, T, J, and K -> G, T, J, K, and V)

Left col. 4th paragraph

- Columns (G, T, J, or K -> G, T, J, K, or V)
- Source code identifier (one-digit -> one -character)

Right col. Hanzi G sources

- Add GE: GB16500-95

Right col. Hanzi T sources

- All sources changed

Right col. Hanja K sources

- Add K2: PKS C 5700-1 1994

Right col. ChuNom V sources

- Add all description